




Toilet installation manual (wall - drainage)



Install the water supply angle valve equipped with the toilet (if there is an old angle valve, please remove it).
The center of the sewage outlet is 180mm above the ground.
*Please close the main inlet valve before installation to avoid water leakage.
Insert the toilet drain straight pipe into the toilet drain pipe on the tiled wall as shown in Figure ①.
Note: Make sure to insert it in place!




Block the toilet drain pipe with a vertical wooden board in an appropriate position and draw a line with a pencil. After the line is drawn, it needs to be pulled out, as shown in Figure ②.




Insert the toilet drain straight pipe and rubber ring into the toilet drain outlet as shown in Figure ③.
Note: Make sure to insert it in place!




Block the toilet drain pipe with a vertical wooden board in an appropriate position and draw a line with a pencil. After the line is drawn, it needs to be pulled out, as shown in Figure ④.




After drawing the assembly line between the toilet drain straight pipe and the toilet drain pipe and the wall mounted toilet drain outlet, mark the actual size (which is the excess part), as shown in Figure L1.




Move the excess part of the middle size of the toilet drain pipe to the edge, add 3mm before sawing it off, as shown in Figure ⑥.




Use a file to chamfer the edge of the toilet drain pipe evenly, as shown in Figure ⑦.




Apply appropriate silicone oil to the "sewage pipe rubber ring as shown in Figure ⑧ and the toilet sewage straight pipe as shown in Figure ⑨".



Insert the toilet drain straight pipe into the toilet drain pipe opening on the wall as shown in Figure ⑨.
Note: Make sure to insert it in place!



Align the toilet drain straight pipe and rubber ring with the toilet drain outlet before inserting them, ensuring that they are inserted in place.



After installing the toilet, do not move it or shake it left or right, as this may damage the sealing of the toilet drain pipe and rubber ring, causing water leakage.
Apply glass glue around the bottom of the toilet to secure it.